


Not recommended for new designs  
The camera model is no longer recommended for new application development.



Specification

Sensor

|                                         |                      |
|-----------------------------------------|----------------------|
| Sensor type                             | CMOS Mono            |
| Shutter                                 | Global Shutter       |
| Sensor characteristic                   | Linear               |
| Readout mode                            | -                    |
| Pixel Class                             | 2 MP                 |
| Resolution                              | 2.35 Mpix            |
| Resolution (h x v)                      | 1936 x 1216 Pixel    |
| Aspect ratio                            | 16:10                |
| ADC                                     | 12 bit               |
| Color depth (camera)                    | 12 bit               |
| Optical sensor class                    | 1/2.3"               |
| Optical Size                            | 6.679 mm x 4.195 mm  |
| Optical sensor diagonal                 | 7.89 mm 1/2.3"       |
| Pixel size                              | 3.45 µm              |
| Manufacturer                            | Sony                 |
| Sensor Model                            | IMX392LLR-C          |
| Gain (master/RGB)                       | 16x/-                |
| AOI horizontal                          | same frame rate      |
| AOI vertical                            | increased frame rate |
| AOI image width / step width            | 256 / 8              |
| AOI image height / step width           | 1 / 1                |
| AOI position grid (horizontal/vertical) | 8 / 1                |
| Binning horizontal                      | increased frame rate |
| Binning vertical                        | increased frame rate |
| Binning method                          | M/C automatic        |
| Binning factor                          | 2x2                  |
| Decimation (subsampling) horizontal     | same frame rate      |
| Decimation (subsampling) vertical       | same frame rate      |
| Decimation (subsampling) method         | M/C automatic        |
| Decimation (subsampling) factor         | 2, 4, 8              |



### Model

|                                   |                    |
|-----------------------------------|--------------------|
| Frame rate freerun mode           | 166 fps            |
| Frame rate trigger (continuous)   | 166 fps            |
| Frame rate trigger (maximum)      | 166 fps            |
| Exposure time (minimum - maximum) | 0.023 ms - 2000 ms |
| Long exposure (maximum)           | 30000 ms           |
| Power consumption                 | 2.1 W - 4.3 W      |
| Image memory                      | 128 MB             |

### Ambient conditions

For PCB versions, refer to the separate hints in the respective documentation.

|                                             |                                 |
|---------------------------------------------|---------------------------------|
| Allowed device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F   |
| Allowed device temperature during storage   | -20 °C - 60 °C / -4 °F - 140 °F |
| Humidity (relative, non-condensing)         | 20 % - 80 %                     |

### Connectors

|                     |                                           |
|---------------------|-------------------------------------------|
| Interface connector | USB Type-C                                |
| I/O connector       | 8-pin Hirose connector (HR25-7TR-8PA(73)) |
| Power supply        | USB cable                                 |

### Pin assignment I/O connector

|   |                                              |
|---|----------------------------------------------|
| 1 | Ground (GND)                                 |
| 2 | Flash output with optocoupler (-) - Line 1   |
| 3 | General Purpose I/O (GPIO) 1, 3.3 V - Line 2 |
| 4 | Trigger input with optocoupler (-) - Line 0  |
| 5 | Flash output with optocoupler (+) - Line 1   |
| 6 | General Purpose I/O (GPIO) 2, 3.3 V - Line 3 |
| 7 | Trigger input with optocoupler (+) - Line 0  |
| 8 | Output supply voltage, 5 V (100 mA)          |



### Design

|                  |                             |
|------------------|-----------------------------|
| Lens Mount       | C-Mount                     |
| IP code          | -                           |
| Dimensions H/W/L | 34.0 mm x 44.0 mm x 31.0 mm |
| Mass             | 46 g                        |
| Housing material | -                           |

### Features

List of on-camera image pre-processing features.

All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

#### Image Acquisition

|                             |   |
|-----------------------------|---|
| Freerun                     | ✓ |
| Software trigger            | ✓ |
| Hardware trigger            | ✓ |
| Trigger controlled exposure | ✓ |
| Denoiser                    | ✓ |
| Long exposure               | ✓ |
| Line scan                   | ✓ |

#### Flashing

|              |   |
|--------------|---|
| Flashing     | ✓ |
| PWM flashing | ✓ |

## U3-30C1SE-M-GL (AB03428)

### Image Adjustments

|                   |     |
|-------------------|-----|
| Auto exposure     | ✓   |
| Auto gain         | ✓   |
| Auto whitebalance | -   |
| Color correction  | -   |
| Gamma             | ✓   |
| LUT               | ✓   |
| Mirror/flip       | X/Y |

### On-board Image Processing

|                     |                                                 |
|---------------------|-------------------------------------------------|
| Pixel formats       | Mono8<br>Mono10<br>Mono10p<br>Mono12<br>Mono12p |
| Region of interest  | ✓                                               |
| Decimation (FPGA)   | ✓                                               |
| Decimation (Sensor) | -                                               |
| Binning (FPGA)      | ✓                                               |
| Binning (Sensor)    | 2x2<br>Increases frame rate.                    |

### Others

|                                |     |
|--------------------------------|-----|
| Chunks                         | ✓   |
| Sequencer                      | -   |
| Events                         | ✓   |
| Firmware update                | ✓   |
| 1st supported firmware version | 2.9 |